



Carpets for Kids® Printed Collection

YARN SPECIFICATIONS

Description	Cut pile carpet
Traffic	Commercial
Warranty	Lifetime Abrasive Wear
Fiber Type	100% Continuous Filament Type 6 Nylon

FABRIC FINISHING	
Dye Method	Dye Injection Print
Soil Release Treatment	Fluorocarbon

FABRIC CONSTRUCTION	
Finished Face Weight	24 oz. / sq. yd.
Yarn Ply	2 ply
Stitches/Rows	8.66/inch
Gauge	1/10 ga.
Finished Pile Height	0.312 inches
Primary Backing	Polypropylene
Secondary Backing	KIDply® with Antimicrobial

PERFORMANCE SPECIFICATIONS	
Density	2769
Weight Density	99,692
<u>Traffic Performance</u>	
Static Electricity	AATCC-134
Traffic	Recommended for residential & commercial



Flammability

Radiant Panel	>.45 watts/cm. sq. (ASTM-E648 <u>Class 1</u>)
NBS Smoke Chamber	<450 flaming & nonflaming (ASTM-E662 NFPA-258)
Methanimine Tablet	Self extinguishing (DOC-FF-1)

1. Specifications subject to normal manufacturing tolerances and may be changed without prior notice.
2. Acceptance of orders subject to Carpets for Kids conditions of sale.
3. Serging excluded from Lifetime Abrasive Wear Warranty.