



PLEASE NOTE:

- 1) FOR SAFE OPERATION AND CONTINUED HIGH PERFORMANCE FROM THIS EQUIPMENT, INSPECTION AND MAINTENANCE MUST BE PERFORMED BEFORE EACH USE
- 2) USE OF THIS EQUIPMENT OTHER THAN INTENDED, MAY BE HAZARDOUS.
- 3) ALTERATION OR MODIFICATION OF EQUIPMENT MAY BE HAZARDOUS. FOR REPAIR OR REPLACEMENT, PLEASE CALL YOUR DEALER

| | | |
|--|--|--|
| <h1>Jaypro Sports</h1> <p>976 Hartford Turnpike Waterford, CT 06385 USA (800)243-0533 (800)988-3363 Fax www.jaypro.com</p> | <p>MODEL NO.:</p> <h2>PB-20</h2> | |
| | <p>PRODUCT NAME:</p> <p>15' PLAYERS BENCH WITH BACK REST</p> | |
| | <p>DRAWN BY: JAC</p> | <p>EFFECTIVE DATE:</p> <h3>5-1-03</h3> |

JAYPRO SPORTS

15' PLAYER'S BENCH WITH BACK REST, PB-20

LIST OF MATERIALS

| <u>PIECE NO.</u> | <u>PART NO.</u> | <u>DESCRIPTION</u> | <u>QTY.</u> |
|------------------|-----------------|-----------------------------|-------------|
| 1 | AR5044 | Bolt Clip With Slot | 12 |
| 2 | AR5045 | End Cap | 4 |
| 3 | HB5030 | Carriage Bolt 5/16"-18 X 3" | 12 |
| 4 | HN5046 | 5/16" Flange Nut | 12 |
| 5 | HS5035 | #8 Pan Head Screw x 1/2" | 8 |
| 6 | EP0018 | 2" End Cap | 12 |
| 7 | AR5043 | Seat Plank x 15' | 2 |
| 8 | PB801 | Leg | 3 |

ASSEMBLY INSTRUCTIONS

TOOLS REQUIRED: Phillips Screwdriver Bit With Electric Drill (1),
1/2" Socket Wrench or Adjustable Wrench (1)

- 1) Slip the end caps (2) snugly onto each end of each plank (7). Using the electric drill, assemble a self-drilling screw (5) through the cap and into the flange of the plank. Two screws are required per end cap. Carefully assemble 2" end caps (6) into bench legs (8).
- 2) For easiest assembly, position seat plank (7) on a level raised surface such as a desk top, bleacher seat or work bench. Place the carriage bolt (3) and bolt clips (1) approximately into place within the slots of the plank. Note that the outside legs should be no more than 8" from the plank edge.
- 3) Position the legs (8) as shown and loosely assemble the hardware illustrated in detail 'A-A'. Do not fully tighten the hardware at this time.
- 4) Stand the unit upright and assemble the backrest plank (7) as illustrated. Level the bench and make sure the legs are adequately spaced apart. Tighten all fasteners fully.