



SPECIFICATIONS

ZROCK18 ZUMA® Rocking Chair, 17-5/8" Seat Height

Description: Virco's ZUMA® rocking chairs featuring a sturdy, cantilevered tubular steel frame with a comfortable, ergonomically contoured polypropylene shell that flexes to accommodate different body types include model ZROCK18 with a 17-5/8" seat height. Please note that the ZROCK18 rocking chair is recommended for use on carpeted surfaces only.

Frame: The cantilevered frame's sled-base legs shall be formed from 1" x 12 gauge tubular steel and angled so that a rocking motion will be initiated when a ZROCK18 user moves forward or backward in the chair. The frame shall include a 7/8" x 13 gauge steel seat support tube, which shall be welded on both ends to the formed legs. Two 15 gauge steel seat support brackets shall be welded across the upper portion of the legs and the seat support tube. The seat support brackets shall enable seat attachment by means of six rivets, three on each side.

Plastic Chair Shell: The unit shall have a one-piece, injection-molded polypropylene plastic shell featuring a waterfall front edge to promote good circulation in the user's popliteal arches, lower legs and feet. The carefully relieved seat scoop shall help reduce pressure on the sensitive ischial tuberosities ("bottom bones"), while a generous and flexible thoracic-area surface shall provide excellent mid-back support and comfort to users of many sizes. The gentle lumbar swell in the back shall promote proper reverse curvature of the spine and ensure comfort for a wide range of body types. A hollowed-out "wallet area" shall help prevent uncomfortable pressure on the sacrum and coccyx (tailbone), and encourage good posture. Color shall be evenly dispersed throughout the plastic for a clean and fresh appearance. Both sides of the shell shall be textured and have an attractive handhold in the upper portion of the back with smooth edges for ease of carrying chairs. The seat shall have contoured wrap-around flexible ribs, which are dynamically tuned to allow the upper back to flex more easily than the lower sections, a key to combining comfort with support. The seat shall be

permanently attached to the frame with six steel rivets beneath the seat, eliminating traditional holes and rivets in the seating surface.

Metal Finish: The chair's frame shall be available with a chrome finish.

Glides: The unit shall be equipped with four nylon glides, two of which cover the ends of the frame tubes.

Dimensions:

ZROCK18
Seat ht. 17-5/8"
22-3/8"D x 20"W x 30-5/8"H

Rocking Range (from "at rest" position):
Approximately 9 degrees of forward motion.
Approximately 10 degrees of backward motion.