



SPECIFICATIONS

9260PGC 9000 Series Adjustable Mobile Chair, Padded Seat & Back

Description: Virco's 9000 Series includes the model 9260GC adjustable-height pedestal base mobile chair with a one-piece molded polyethylene shell, upholstered seat and back pads and a pneumatic cylinder.

Frame: A steel back support made of a continuous length of 3/4" x 17 gauge steel tubing shall be welded to a 12 gauge steel attaching plate. An 8 gauge steel swivel plate shall attach to the attaching plate with 4 machine screws and nuts plate for mating to the pneumatic cylinder.

Pneumatic Cylinder: This shall consist of a gas-filled cylinder with a steel piston and housing. The piston shall be tapered to pressure fit into the unit's swivel plate and pedestal base. The cylinder shall permit the chair to swivel 360°.

Plastic Shell: This shall consist of injection molded polyethylene to a posture enhancing form with rolled edges and a reinforced area at rivet points. The plastic shall have an additive to dispel static charge from product. Color shall be evenly dispersed throughout the plastic for a clean and fresh appearance. The face of the shell shall have three ventilation slots and shall be textured to promote good posture. The shell shall be attached to the frame with four steel nickel-plated rivets.

Upholstered Pads: These shall consist of 5/8" thick polyurethane foam, covered with fabric that shall be bonded to a high density polyethylene frame. Pads shall be affixed to shell with twelve pop rivets.

Pedestal Base: This shall consist of fiberglass-reinforced nylon and have a five-prong construction. The base shall accept the unit's pneumatic cylinder and casters, or optional fixed glides.

Casters: The chair shall have five dual-wheel 2" hooded swivel casters constructed of high-impact nylon with steel stems and lock-fit expansion rings. Optional soft wheel casters or glides shall be available for field installation only. For soft wheel casters, specify "U9024CAST"; for glides, specify "UGLIDE".

Adjustment Range: Seat height shall be adjustable from 18" to 22-5/8". The overall height of this unit shall be adjustable from 30-1/4" to 34-7/8".

Metal Finish: The unit's metal surfaces shall be available with a powder coat finish.

Dimensions:

9260PGC

Height: See Adjustment Range paragraph.

Depth: 25"

Width: 25"