

Stage steps shall have the following construction standard features and benefits.

MODELS:

- **STP1:** 1 Step— for 8" high
- **STP2:** 2 Steps— for 8"/16" high
- **STP3:** 3 Steps— for 8"/16"/24" high

FINISH

WIDTH: 35"

DEPTH: 31" OR 32" OR 40"

HEIGHTS: 40" OR 48" OR 56"

FINISH

All metal parts are thoroughly cleaned and electrostatically sprayed with a high grade powder paint and baked in temperature controlled ovens to obtain a high quality finish.

STEPS

Each step is constructed of finished polyethylene step tread, 30" wide x 15" deep. Each step is supported by steel cross members, consisting of **1-1/16" square**, 14 gauge steel tubing. (Carpeted steps as an option.)

SAFETY HAND RAIL

All safety hand rail frames shall be constructed of heavy-duty 14 gauge x 1-1/4" **square** steel tubing.

WHEELS

Step unit shall be equipped with two, 2" x 1" non-swivel casters welded in place to allow for easy portability.

SAFETY

Guard rails are constructed of 14 gauge steel tube attached with 2" steel mounting plate for strength and durability.

STAGE CONNECTION

Each stage step unit shall be able to lock into the stage with a steel hook mechanism. No tools required.

MAS GREEN CERTIFICATION

Stage stairs shall be tested and certified for indoor air quality, for public safety as well as environmental protection.

WARRANTY

Stage stairs shall be covered by a 15 year warranty.

All weld joints shall be covered by a lifetime warranty.

